

OMNI-SOLUTIONS



Description

Datalogic's flexibility in designing omni-directional reading systems makes it possible to always have the right product in the right spot, assuring an effective solution for any application specification. The combination of vision and laser technologies means being able to satisfy the customer's needs with the ideal solution and the best price/performance ratio. The laser solution can be scaled in accordance with conveyor speed, reading area and other relevant specifications. The resulting system is designed with the ideal combination of the DS8100A and DX8200A. The SC6000 controller collects and elaborates data received by the scanner, and provides users with a unique standard interface. Each device that makes up the omni-directional reading system has

been designed to assure easy maintenance without requiring an expert scanner technician. Furthermore, the System Supervisor monitoring software allows remote monitoring, in real time, of the omni-directional reading systems and advises when maintenance is required.

- Products**
- DV9500
 - DS8100A
 - DX8200A
 - SC6000

Features

- Multi-side omni-directional barcode reading
- Serial, Ethernet, Profibus, Devicenet communication
- Quick maintenance without the need of an expert technician
- MTTR (of each device in the solution) in less than 10 minutes
- Full diagnostics and statistics available
- Sentinel supervisor software for remote monitoring

SYSTEM SUPERVISOR SW



Datalogic WebSentinel™ SW supervisor offers a complete remote surveillance and control of a plant with a large number of multisided reading arrays. It collects data from the arrays through an Ethernet TCP/IP bus; it computes the received information flow as intuitive visual onscreen data and makes them accessible through the Internet. Datalogic WebSentinel™ offers extended statistic and diagnostic information at plant, array and single scanner level. Ease of use is highly improved thanks to the multi-language capability system (English, Japanese, Korean, German, Italian, French, Spanish). Web Browser data access guarantees the ease of a standard access throughout any PC connected to the Internet. Scanning

system control, configuration and monitoring are easier than ever thanks to the Genius™ passthrough feature, which allows direct remote access even to the single device level. Datalogic WebSentinel™ supports all the main Datalogic products and can be configured up to 256 arrays on the plant.

- Multiple reading systems surveillance and monitoring
- Ideal base for maintenance programs
- Extended Diagnostics and Statistic
- Multilanguage support
- Remote data access through Web-browser
- Remote Maintenance through Genius™ integration
- Multiple-users support
- Supports up to 256 arrays

SERVICE



Technical support

Datalogic Automation offers to its customers a wide range of formulas to take care of their products. **EASEOFCARE** is the new service of Datalogic Automation: it provides on line management of product repairs, including collection service from customers. **EASEOFCARE** supplies all the information needed to open an MRA (Material Return Authorization), product shipment, repair checking and repair fee payment.

Datalogic Automation, through its technical support services and teams, plans and implements the barcode reading station to ensure that its products are installed and used in the best possible way. Service includes: preventive maintenance, emergency calls and processing of customer needs. Datalogic Automation has a network of over 100 certified Partners ensuring pre and post sales support worldwide.

Unattended Scanning Systems
Product Range



Bar Code Readers, Imagers and Vision Systems for Embedded and Industrial Solutions



DATALOGIC AUTOMATION SRL
Via S. Vitalino n. 13
Lippo di Calderara di Reno
Bologna 40012 Italy

Tel. +39 051 3147011
Fax +39 051 3147453


www.automation.datalogic.com

Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements.



May 2008






EMBEDDED BAR CODE READERS

Applications	Features	Specifications
<p>DS1100</p>  <ul style="list-style-type: none"> Access control systems Game automation (Lotto, Lottery, etc.) Chemical and biomedical analysis machines ATL (Automated Tape Library) Self Service Systems (ATM, Kiosk) Video rental machines Printing machines Small conveyors and picking systems Film processing machines Work-in-progress and Quality control High speed pharmaceutical Packaging Document Handling machine Packaging machine 	<ul style="list-style-type: none"> Cost effective Excellent reading capabilities Wide reading width at a short reading distance Very compact dimensions Designed for OEM integration ACB™ Advanced Code Builder technology (DS1500) Code reconstruction software embedded (TC1100) Motor on/off SW control Easy configuration via Windows-based programming tools Easy set up through WINHOST™ Very high density code reading (up to 0.076 mm / 3 mils) (DS2200) 	<p>TC1100</p> <ul style="list-style-type: none"> CCD readers Scan Rate: 270 scans/s Reading Range: 35 to 310 mm Max Resolution: 0.076 mm (3 mils) "All in One" architecture: RS232/Wedge/Pen Power Supply: 5 Vdc <p>DS1100</p> <ul style="list-style-type: none"> Scan Rate: 500 scans/s Reading Range: 10 to 220 mm Max Resolution: 0.12mm (5 mils) Motor on/off via software commands Power Supply: 5 Vdc <p>DS1500</p> <ul style="list-style-type: none"> Ultra compact dimensions: 40x30x22 mm Scan Rate: 1200 scans/s Reading Range: 40 to 240 mm Max Resolution: 0.15 mm (6 mils) Test mode with bar graph Power Supply: 5 Vdc <p>DS2200</p> <ul style="list-style-type: none"> Scan Rate: 500 (up to 2000) scans/s Reading Range: 50 to 200 mm Max Resolution: 0.076 mm (3 mils) Power supply: 5Vdc, 2W max Protection class: IP65


INDUSTRIAL BAR CODE READERS

<p>DS2100N DS2400N</p>  <ul style="list-style-type: none"> Packaging machines Chemical and biomedical analysis machines Automated shopfloor Items and parts tracking Packaging and compliance Automated warehousing Conveyor sorting Label verification Picking systems High speed pharmaceutical packaging High speed document handling Reverse Vending Machines (Cans and Bottles recycling) 	<ul style="list-style-type: none"> Intuitive X-PRESS™ Human Machine Interface ID-NET™ embedded interface for high-speed communication network ACB™ Advanced Code Builder technology Compact dimensions for direct and 90° reading Ambient light immunity through high frequency laser modulation Reading distance up to 600 mm Multi-language Genius™ SW Tool allows rapid scanner configuration 	<p>DS2100N</p> <ul style="list-style-type: none"> Scan rate: Up to 1000 scans/s Reading range: 30 to 310 mm Max resolution: 0.12 mm (5 mils) Power Supply: 10 to 30 Vdc, 5W max Protection class: IP65 <p>DS2400N</p> <ul style="list-style-type: none"> Scan Rate: 400 to 1000 scans/s Reading Range: 60 to 600 mm Max Resolution: 0.20 mm (8 mils) Power Supply: 10 to 30 Vdc, 5W max Protection class: IP65
<p>DS4800</p>  <ul style="list-style-type: none"> Shop Floor and automated warehousing Medium / small conveyor sorting Reading on pallets Picking systems Items and parts tracking Process control systems 	<ul style="list-style-type: none"> Smart Focus adjustment for flexible reading area selection DIGITECH™ technology allows excellent reading performance Intuitive X-PRESS™ Human Machine Interface ID-NET™ embedded interface for high-speed communication network ACR4™ reconstruction technology improves reading of damaged barcodes Multi-language Genius™ SW Tool allows rapid scanner configuration Multi-language display improves scanner monitoring and diagnostic Total ambient light immunity thanks to the high frequency laser modulation 	<p>DS4800</p> <ul style="list-style-type: none"> ACR4™ Advanced Code Reconstruction Scan Rate: up to 1000 scans/s Reading Distance: up to 1000mm on 0.50mm (20 mils) codes Depth Of Field: Up to 600mm on 0.50mm (20 mils) codes Max Resolution: Up to 0.20 mm (8 mils) Connectivity: RS232, RS485 I/O: 2 Inputs, 2 Outputs; optocoupled Power Supply: 10 to 30 Vdc; 6W max Protection Class: IP65




INDUSTRIAL BAR CODE READERS

<p>DS6300 DS6400</p>  <ul style="list-style-type: none"> Automated warehousing Reading on forklift trucks Electronic industry manufacturing Shop floor on Automotive, Electric Appliances, Food & Beverage Sorting on Logistics and Distribution lines Reading in airports: induction line and main sorters Omni-sorting on small conveyors 	<ul style="list-style-type: none"> Modular solution based on a reading HEAD and decoder BASE Reading distance up to 2500 mm Adjustable, Flash™ (Dynamic), laser optics Step-A-Head™ feature ACR4™ code reconstruction technology Integrated oscillating mirror available Built-in connectivity to Ethernet/Devicenet/Profibus PackTrack™ tracking system Display and keypad Multi-language Genius™ SW Tool allows rapid scanner configuration 	<p>DS6300</p> <ul style="list-style-type: none"> ACR4™ Advanced Code Reconstruction Scan Rate: Up to 1200 scan/sec Reading Range : 300 to 2000 mm Power Supply: 15 to 30 Vdc, 15W max Optics: Adjustable <p>DS6400</p> <ul style="list-style-type: none"> ACR4™ Advanced Code Reconstruction Scan Rate: Up to 1200 scan/sec Reading Range : 300 to 2500 mm Power Supply: 15 to 30 Vdc, 15W max Optics: Flash™ (dynamic)
<p>DS8100A</p>  <ul style="list-style-type: none"> Postal and courier automatic parcel sorting and tracking Goods sorting and tracking in distribution centers Baggage Handling System in airport facilities Parcel identification in DWS systems (cubing, weighing and data capture) Cargo applications Loading/unloading systems 	<ul style="list-style-type: none"> Market benchmark for fixed position laser scanners ASTRA™ multi-laser electronic focussing system Automatic bar code distance measurement ACR4™ code reconstruction technology PackTrack™ tracking system Ambient light immunity Designed for top performance in Sorting applications Display & keypad Built-in connectivity to Ethernet, Profibus and Devicenet Multi-language Genius™ SW Tool allows rapid scanner configuration 	<p>DS8100A</p> <ul style="list-style-type: none"> Laser Pattern: Single Scan Rate: 1000 scans/s Reading Range: 500 to 2000 mm Max Resolution: 0.2 mm (8 mils) Dimensions: 215.5 x 170.5 x 126.5 mm (8.5 x 6.7 x 5.0 in) Protection Class: IP64 (IP65 optional) Operating temperature: 0 to 50° C <p>DS8200A</p> <ul style="list-style-type: none"> Laser Pattern: Cross Scan Rate: 1000 scans/s (500 each scan line) Reading Range: 500 to 1500 mm Max Resolution: 0.2mm (8 mils) Dimensions: 470 x 300 x 147 mm (18.5 x 11.8 x 5.78 in) Protection Class: IP64 (IP65 optional) Operating Temperature: 0 to 50° C
<p>DX8200A</p> 		


VISION SYSTEM

<p>DV9500</p>  <ul style="list-style-type: none"> Outstanding decoding performance on low quality labels under plastic film High reading performance on high speed conveyors Multi-side modular solution Linear CCD technology Advanced patented auto-focus system Image saving capability Easy replacement concept Diagnostics and remote control Easy integration with laser systems 	<ul style="list-style-type: none"> Postal and logistics applications Distribution applications Garment and Multimedia sorting Reverse Logistic Processes Suitable for OCR and Video-coding 	<p>DV9500</p> <ul style="list-style-type: none"> CCD Sensor: 6144 pixels, 4 taps Image Resolution: 110 to 260 dpi, (application dependent) Conveyor Coverage: Up to 1100 mm (43 in) Depth of Field: Up to 1000 mm (39 in) Conveyor Speed: Up to 3.0 m/s Linear codes read: Code 128, Code 39, Interleaved 2/5, EAN/UPC and all popular barcodes 2D codes read: PDF417, Datamatrix and all popular 2D codes, postal codes Output data: Decoded label, high quality images Data Output: Serial, Ethernet, Profibus, Devicenet Video Output: Camera Link, 16/32 bit LVDS Robust industrial architecture and dust-proof design
---	---	--


IMAGERS

<p>MATRIX 200™</p> 	<ul style="list-style-type: none"> WIP control/product traceability Direct Part Marking (DPM) reading and verification Document and mail processing CD/DVD identification Reverse Logistic Processes PCB and Semiconductor production line tracking Chemical and biomedical analysis machines Small objects/ pharmaceutical packaging 96 vials rack reading 	<p>CCD/CMOS based 2D reader for fixed industrial applications</p> <ul style="list-style-type: none"> Compact industrial unit integrating lighting, image capturing, decoding and communication Direct or 90° reading window 1D & 2D, stacked, composite, postal code reading Autolearning function Code quality control (ISO-IAQG) External Illuminators available as accessories Intuitive X-PRESS™ Human Machine Interface ID-NET™ embedded interface for high speed communication network Adjustable focus through C-Mount lenses (MATRIX 400™) Blue Diamonds™ aiming and focusing system (MATRIX 400™) USB connectivity (MATRIX 200™) <p>MATRIX 200™</p> <ul style="list-style-type: none"> CMOS matrix sensor WVGA image resolution Read Rate: up to 60 frames/s Object speed: up to 2.0 m/s Connectivity: RS232, RS485, USB I/O: 2 Inputs, 2 Outputs; optocoupled Power Supply: 10 to 30 Vdc or 5 Vdc; 2.5W max Protection Class: IP65 <p>MATRIX 400™</p> <ul style="list-style-type: none"> CMOS/CCD matrix sensors SXGA/UXGA image resolution Read Rate: up to 27 frames/s Object Speed: up to 6.0 m/s Connectivity: RS232, RS485, Ethernet I/O: 2 Inputs, 3 Outputs; optocoupled Power Supply: 10 to 30 Vdc; 8W max Protection Class: IP67 <p>MATRIX-2000™</p> <ul style="list-style-type: none"> CCD matrix sensor VGA image resolution Read Rate: up to 60 frames/s Object speed: up to 6.0 m/s Connectivity: RS232, RS485, Ethernet I/O: 2 Inputs, 3 Outputs; optocoupled Power Supply: 10 to 30 Vdc; 8W max Protection Class: IP64
<p>MATRIX 400™</p> 		
<p>MATRIX-2000™</p> 		

CONTROLLERS

<p>SC6000</p> 	<ul style="list-style-type: none"> Sorting for Transportation & Logistics (Express Couriers, Postal applications) Sorting for Distribution (large Logistic/Distribution Centers) Sorting for Baggage Handling Systems 	<ul style="list-style-type: none"> Industrial controller for multi-side reading stations DARP™ (Datalogic Automatic Replacement Procedure) function High performing CPU GÉNIUS™ configuration program Display and 6-key keypad for diagnostics/statistics Built-in Ethernet, Profibus and Devicenet connectivity Modem connection <p>SC6000</p> <ul style="list-style-type: none"> Main Feature: Based on Genius™ SW platform Compatibility: 6000/8000 scanner families Display: 4 lines x 20 characters Connectivity : Ethernet, Devicenet, Profibus Power Supply: 24 Vdc MX4000 Main features: Data collection on RS485 bus Connectivity: Profibus/DP Remote control and configuration Power supply: 10 to 30 Vdc
---	--	--

CONNECTIVITY

<p>CBX SERIES</p> 	<ul style="list-style-type: none"> Manufacturing Shop Floor Warehousing 	<ul style="list-style-type: none"> IP65 (NEMA 4) rated industrial design Flexible mounting and simplified wiring to speed up the installation Reliable Backup and Restore feature to minimize plant downtime Comfortable connectivity to Ethernet, Profibus and DeviceNet network with open architecture for extensions Multilanguage Display for easy monitoring and troubleshooting Visible Power and I/O indicators and convenient Power on/off switch Code reader diagnosis and monitoring through display <p>CBX SERIES</p> <ul style="list-style-type: none"> Display: 4 lines x 20 characters Power Supply: 10 to 30 Vdc, 2.5W max Protection Class: IP65 (NEMA4) Operating Temperature: -10 to 50°C
--	--	---